

# Core Switch VRRP Linkage





## Overview

---

Deploy VRRP between SwitchA and SwitchB to implement link redundancy at the aggregation layer. Configure basic MSTP functions (SwitchA, SwitchB, SwitchC, and SwitchD are used as examples). VRRP allows for transparent failover at the first-hop IP router, by configuring a group of routers to share a virtual IP address. VSs need to be created on the CE12800 to function as core and aggregation switches and set up a three-layer network structure with one core switch, two aggregation switches, and multiple access switches. Routers are CCR2004 which doesn't have any switch chip, in order to not waste CPU on layer 2 traffic, I didn't configure bridge and vlan on the router. This product includes code licensed under certain open source licenses which require source compliance.



## Core Switch VRRP Linkage

---

# Virtual Router Redundancy Protocol (VRRP)

---

Virtual Router Redundancy Protocol (VRRP) VRRP is a first hop redundancy protocol (FHRP). It provides gateway redundancy by enabling a pair of VRRP routers to coordinate and act as one

## Deploying VRRP on a Data Center Network with 2-Layer Architecture

---

Deploy VRRP between SwitchA and SwitchB to implement link redundancy at the aggregation layer. Deploy MSTP between access and core layers to eliminate loops. Configure basic MSTP functions



## VRRP Configuration

---

**Definition** The Virtual Router Redundancy Protocol (VRRP) is a standard-defined fault-tolerant protocol that groups several physical routing devices into a virtual one. If a physical routing device (master)

## Configuring a Data Center Network Based on VS and VRRP

---

On the data center network shown in Figure 1-3, a CE12800 connects to multiple access switches. VSs need to be created on the CE12800 to function as core and aggregation switches and set up a three

## STP for LACP Trunks at Core1, Core2 (VRRP enabled) and Edge Switches

---



Edge switch has redundant LACP Trunks to core1 and core2 through Trunk5 and Trunk25 respectively. As i made the trunks, it automatically assigned Priority4 for all the Trunks at

## Chapter: Configuring VRRP

---

This chapter describes how to configure the Virtual Router Redundancy Protocol (VRRP) on Cisco Nexus 9000 Series switches running Cisco NX-OS Release 9.x.

## AOS-CX 10.13 Virtual Switching Extension (VSX) Guide

---

Aruba Virtual Switching Extension (VSX) is virtualization technology for aggregation/core switches running the AOS-CX operating system. This solution lets the switches present as one virtualized



## Configuring VRRP Virtual Routers on a SG550XG

---

This article provides instructions on how to configure VRRP settings on your switches through the Command Line Interface (CLI).

## 6300M Core (Stacked or VRRP?) : r/ArubaNetworks

---

6300M Core (Stacked or VRRP?) Aruba spec'd out a 6300M core for our corporate office build. In the design it's a pair of stacked switches. Thought this was a bit odd in lieu of using a redundancy

## How To Configure VRRP (Virtual Router Redundancy Protocol)

---

The core switches are also running VRRP to provide router redundancy for end devices such as the PCs and servers. The end devices are connected to the core switches



through Layer 2 distribution switches.

## VRRP with VSX configuration

---

One VSX switch acts as a VRRP Active router and the other switch acts as the VRRP Standby. Both VSX switches route the traffic. The active gateway/VRRP configuration must be consistent across

## Is it possible to have VRRP configured on core switches (ms425

---

Is it possible to have VRRP configured on core switches (ms425) that are on different buildings? There will be fibre connection between them.



## vrrp configuration with fully redundant switches

---

Yeah, MLAG with VRRP might do. I have already reduced the complexity of this topology, there just 2 links goes between core switches and routers, hence I only need to have 1 vrrp IP, I have

## Configuring VRRP and VRRPE

---

Configuring VRRP and VRRPE This chapter describes how to configure HP Routing Switches to configure the following router redundancy protocols:

## VRRP for HA or stack core switches

---

400 devices on the network is definitely big enough to justify having a nice VRRP core, with each of your access switches patching back to both physical cores. These frees up your 3750s



## VRRP for HA or stack core switches

---

We have a pair of Cisco Cat 9500 - 16x with network essential license, we don't have a budget to upgrade the license to Network Advantage. We are currently using Cisco 3750 as our core,

## Switch Engine v33.2.1 User Guide

---

Switches A and B in the above figure are each configured with two VRRP router instances. Switch A is the IP address owner and default master for VRRP instance 1, and Switch B is the IP address owner

## Configuring VRRP

---



VRRP interoperates with virtual port channels (vPCs). vPCs allow links that are physically connected to two different Cisco Nexus 5000 Series switches to appear as a single port channel by a third switch.

## Configuring VRRP

---

About VRRP VRRP allows for a transparent failover at the first-hop IP router by configuring a group of routers to share a virtual IP address. VRRP selects an allowed router in that group to handle all

## Configuring VRRP

---

VRRP interoperates with virtual port channels (vPCs). vPCs allow links that are physically connected to two different Cisco Nexus 9000 Series switches to appear as a single port channel by a third device.



## **Deploying VRRP on a Data Center Network with 2-Layer Architecture**

---

Deploying VRRP on a Data Center Network with 2-Layer Architecture Applicable Products and Versions CloudEngine series switches running V100R001C00 or later versions For details about the mapping

## **Deploying VRRP on a Data Center Network with 3-Layer Architecture**

---

Deploying VRRP on a Data Center Network with 3-Layer Architecture Applicable Products and Versions CloudEngine series switches running V100R001C00 or later versions USG5500 series products

## **vrrp configuration with fully redundant switches**

---



I configured vrrp in the router for the redundancy, but due to the topology, each router have 2 connections from switch, so I configured the 4 vrrp interfaces for each physical interface.

## Contact Us

---

For datasheets, pricing, or custom optical networking solutions, please visit:  
<https://entrenamientointeligente.es>