

Huijue Multimode Spectrometer





Huijue Multimode Spectrometer

High-resolution optical spectroscopy using multimode

Multimode interference spectroscopy is suitable in a variety of device geometries, including planar waveguides in a broad range of transparent materials.

Single-Pixel Multimode Fiber Spectrometer via Wavefront Shaping

Download Citation , On Jul 13, 2023, Sahin Kurekci and others published Single-Pixel Multimode Fiber Spectrometer via Wavefront Shaping , Find, read and cite all the research you need on ResearchGate



Applications of multimode fibers for spectroscopy and polarization control

A multimode fiber spectrometer is developed with ultrahigh resolution and extreme broad bandwidth. Shaping the input wavefront enables an effective control of output polarization states of a multimode

Multimode fiber based spectrometer

A multi-mode fiber functions as a high-resolution, low-loss spectrometer. Wavelength-dependent speckle patterns are used for spectrum recovery. Record-high resolution and extremely broad range of

Broadband multimode fiber spectrometer



A general-purpose all-fiber spectrometer is demonstrated to overcome the trade-off between spectral resolution and bandwidth. By integrating a wavelength division multiplexer with five

On-chip Imaging Spectrometer using Multi-mode Interference

A novel on-chip spectrometer based on top-down imaging of a multi-mode interference waveguide is introduced. Accurate wavelength identification with 0.5 nm resolution is demonstrated using a

Compact silicon multimode waveguide spectrometer with enhanced

Abstract Compact, broadband, and high-resolution spectrometers are appealing for sensing applications, but difficult to fabricate. Here we show using calibration data a spectrometer based on a



High-resolution optical spectroscopy using multimode

PDF file

TFMMI_140723 - arXiv

Figure 1 Figures of merit of several compact spectrometers employing detector arrays, including the tapered fiber multimode interference (TFMMI) spectrometer that is described in this work.

[1602.06278] Broadband multimode fiber spectrometer

A general-purpose all-fiber spectrometer is demonstrated to overcome the trade-off between spectral resolution and bandwidth. By integrating a wavelength division multiplexer with five



Compact Spectrometer Based on a Multimode Silicon Waveguide Device

A highly compact spectroscopic measurement scheme is proposed based on a fabricated on-chip silicon device that consists of a multimode interference waveguide containing randomly distributed

Multimode optical fiber based spectrometers

Furthermore, the fiber-based spectrometer requires only a multimode fiber and a monochrome CCD camera to record the speckle patterns. Compared to traditional spectrometers, optical fibers are

Multimode fiber spectrometer with scalable bandwidth



Multimode fiber (MMF) spectrometers suffer from the resolution-bandwidth trade-off due to the limited spatial speckle information used for spectral

Broadband and Ultrahigh Resolution Spectrometer Based on a

The invention is a monolithic, compact spectrometer based on multimode interference (MMI) and can simultaneously achieve high resolving power and bandwidth in a simple-to-couple and compact device.

10.1117/2.1201403.005414 Multimode fiber for low-loss and high

Multimode fiber for low-loss and high-resolution spectrometry Brandon Redding and Hui Cao Calibrating wavelength-dependent speckle patterns enables a multi-mode optical fiber to function as a



Mode division multiplexing reconstructive spectrometer with an all

Abstract This study presents a high-accuracy, all-fiber mode division multiplexing (MDM) reconstructive spectrometer (RS). The MDM was achieved by utilizing a custom-designed 3×1 mode-selective

Using a multimode fiber as a compact, high-resolution spectrometer

We demonstrate that a multi-mode fiber can operate as a high-resolution spectrometer after calibrating wavelength-dependent speckle patterns. A 100m fiber provides 1pm resolution and a 4cm fiber



Compact silicon multimode waveguide spectrometer with enhanced

Compact, broadband, and high-resolution spectrometers are appealing for sensing applications, but difficult to fabricate. Here we show using calibration data a spectrometer based on a

Compact silicon multimode waveguide spectrometer with enhanced

Compact, broadband, and high-resolution spectrometers are appealing for sensing applications, but difficult to fabricate. Here we show using calibration data a spectrometer based on a

Multi-mode interference waveguide chip-scale

MMI spectrometer. (a) Schematic overview of the approach. A continuous or discrete



spectral signal is coupled into a chip with a multi-mode

Design Study of Broadband and Ultrahigh-Resolution

A compact broadband and ultrahigh-resolution imaging spectrometer (CBURIS) is presented, which comprises a microlens array, multiple fiber

Single-Pixel Multimode Fiber Spectrometer via Wavefront Shaping

When light passes through a multimode fiber, two-dimensional random intensity patterns are formed due to the complex interference within the fiber. The extreme sensitivity of speckle



High-resolution optical spectroscopy using multimode interference in a

Here we introduce a compact spectrometer based on multimode interference (MMI) that simultaneously achieves high resolving power of $R4104$ ($R4105$) in the visible (near-infrared) spectrum, and

Using a multimode fiber as a high resolution, low loss spectrometer

These spectrometers, however, afford only modest spectral resolution, while suffering high insertion loss and/or low signal to noise ratio (SNR). In this letter, we demonstrate that a conventional multimode

High-resolution optical spectroscopy using multimode



While desirable for compact solutions, the miniaturization of spectrometers comes at the cost of spectral resolution and operating range. Here, Wan et al. propose a tapered fibre multimode

Single-Pixel Multimode Fiber Spectrometer via

Single-Pixel Multimode Fiber Spectrometer via Wavefront Shaping Şahin Körekci *1, 2, S. Süleyman Kahraman 1, 3, and Emre Yüce 1, 2

AI-assisted spectrometer based on multi-mode optical fiber speckle

Speckle patterns at the output end of a multi-mode fiber (MMF) are generated by the interference of eigenmodes propagating along the fiber. A MMF can



Contact Us

For datasheets, pricing, or custom optical networking solutions, please visit:
<https://entrenamientointeligente.es>